UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/529,809	03/30/2005	Hiroyasu Onuki	44471/314245	6250	
23370	7590 10/05/2007		EXAMINER		
	STOCKTON, LLP		SHAFER, RICKY D		
1100 PEACHT ATLANTA, G	REE STREET A 30309		ART UNIT PAPER NUMBER	PAPER NUMBER	
			2872	•	
			MAIL DATE	DELIVERY MODE	
			10/05/2007	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

3/

			_
,	Application No.	Applicant(s)	
	10/529,809	ONUKI, HIROYASU	
Office Action Summary	Examiner	Art Unit	
	Ricky D. Shafer	2872	
The MAILING DATE of this communicatio Period for Reply	n appears on the cover sheet w	ith the correspondence address	
A SHORTENED STATUTORY PERIOD FOR R WHICHEVER IS LONGER, FROM THE MAILIN - Extensions of time may be available under the provisions of 37 C after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory. - Failure to reply within the set or extended period for reply will, by Any reply received by the Office later than three months after the earned patent term adjustment. See 37 CFR 1.704(b).	IG DATE OF THIS COMMUN FR 1.136(a). In no event, however, may a on. period will apply and will expire SIX (6) MO statute, cause the application to become A	CATION. reply be timely filed NTHS from the mailing date of this communication. BANDONED (35 U.S.C. § 133).	
Status			
 1)⊠ Responsive to communication(s) filed on 2a) This action is FINAL. 2b)⊠ 3)□ Since this application is in condition for all closed in accordance with the practice un 	This action is non-final. lowance except for formal ma		
Disposition of Claims			•
4) Claim(s) 1,3,5-7,9,11-14 and 16-18 is/are 4a) Of the above claim(s) 3 is/are withdray 5) Claim(s) is/are allowed. 6) Claim(s) 1,5-7,9,11-14 and 16-18 is/are re 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and an application Papers 9) The specification is objected to by the Example 10) The drawing(s) filed on is/are: a) □	wn from consideration. ejected. and/or election requirement. aminer. accepted or b) objected to		
Applicant may not request that any objection of Replacement drawing sheet(s) including the country. The oath or declaration is objected to by the country of the country o	correction is required if the drawin	g(s) is objected to. See 37 CFR 1.121(d)	
Priority under 35 U.S.C. § 119		,	
12) Acknowledgment is made of a claim for for a) All b) Some * c) None of: 1. Certified copies of the priority docu 2. Certified copies of the priority docu 3. Copies of the certified copies of the application from the International E * See the attached detailed Office action for	iments have been received. Iments have been received in the priority documents have bee Bureau (PCT Rule 17.2(a)).	Application No n received in this National Stage	
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-9-3) Information Disclosure Statement(s) (PTO/SB/08)	48) Paper N	Summary (PTO-413) o(s)/Mail Date Informal Patent Application	

Paper No(s)/Mail Date ___

6) Other: _____.

DETAILED ACTION

- 1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 09/26/2007 has been entered.
- 2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 3. Claims 1, 5 and 6 are rejected under 35 U.S.C. 102(b) as being anticipated by Ishizaki ('020).

Ishizaki discloses a mirror device for a vehicle comprising a hollow shaft (2) that is provided with a mirror base (1) fixed to a vehicle body, a housing (5) which houses a motor (7) for swinging a mirror unit (3) between a use position and a fold position and is turnably supported by the shaft penetrating the housing; and a cover (6) for covering the housing to thereby seal an inside of the housing, wherein the cover includes a cylindrical portion (CP) which extends in the axial direction of the shaft and engages with the outer surface of the shaft when the shaft is inserted into the housing, and an end portion cover (EP) which extends in a first direction substantially perpendicular to the axial direction of the shaft and has a first end at a tip of the cylindrical portion and a second end at a point which covers a penetration end surface of the shaft (see Fig. 1), wherein the cylindrical portion is rotatable relative to the shaft in such a

Application/Control Number: 10/529,809

Art Unit: 2872

Page 3

manner as to be in contact with the shaft (see Fig. 1), wherein the end portion cover and the penetration end surface are configured to define a space there between in the axial direction of the shaft, in such a manner as to be free from contact there between, and the first end and second end of the end portion cover are aligned on a line substantially parallel to the axial direction of the shaft, and wherein the shaft defines an inner cylindrical face which extends to the penetration end surface of the shaft, wherein the end portion cover is part of the cover that covers the motor, and wherein the tip of the cylindrical portion (the rounded portion thereof) is inclined toward the shaft in a free/formed state. Note Fig. 1 along with the associated description thereof.

- 4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 5. Claims 7 and 11-14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ishizaki ('020) in view of Oesterholt et al ('514).

Ishizaki discloses a mirror device for a vehicle comprising a hollow shaft (2) that is provided with a mirror base (1) fixed to a vehicle body, a housing (5) which houses a motor (7) for swinging a mirror unit (3) between a use position and a fold position and is turnably supported by the shaft penetrating the housing; and a cover (6) for covering the housing to thereby seal an inside of the housing, wherein the cover includes a cylindrical portion (CP) which extends in the axial direction of the shaft and engages with the outer surface of the shaft when the shaft is inserted into the housing, and an end portion cover (EP) which extends in a first

Application/Control Number: 10/529,809

Art Unit: 2872

direction substantially perpendicular to the axial direction of the shaft and has a first end at a tip of the cylindrical portion and a second end at a point which covers a penetration end surface of the shaft (see Fig. 1), wherein the cylindrical portion is rotatable relative to the shaft in such a manner as to be in contact with the shaft (see Fig. 1), wherein the end portion cover and the penetration end surface are configured to define a space there between in the axial direction of the shaft, in such a manner as to be free from contact there between, and the first end and second end of the end portion cover are aligned on a line substantially parallel to the axial direction of the shaft, and wherein the shaft defines an inner cylindrical face which extends to the penetration end surface of the shaft, wherein the end portion cover is part of the cover that covers the motor, and wherein the tip of the cylindrical portion (the rounded portion thereof) is inclined toward the shaft in a free/formed state, note Fig. 1 along with the associated description thereof, except for explicitly stating that the cylindrical portion and the end portion cover form substantially an L-shape in cross section.

Oesterholt et al teaches it is well known to use covers having a cylindrical portion which extends in an axial direction of a shaft (101) and an end portion cover which extends in a first direction substantially perpendicular to the axial direction of the shaft, wherein the cylindrical portion and the end portion form substantially an L-shape in cross section (see Fig. 4) in the same field of endeavor for the purpose of obtaining a seal.

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the cylindrical portion and the end portion of Ishizaki to include a L-shape configuration in cross section, as taught by Oesterholt et al, in order to reduce space and the manufacturing costs.

Art Unit: 2872

6. Claims 9 and 16-18 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ishizaki ('020) in view of Oesterholt et al ('514).

Ishizaki discloses a mirror device for a vehicle comprising a hollow shaft (2) that is provided with a mirror base (1) fixed to a vehicle body, a housing (5) which houses a motor (7) for swinging a mirror unit (3) between a use position and a fold position and is turnably supported by the shaft penetrating the housing; and a cover (6) for covering the housing to thereby seal an inside of the housing, wherein the cover includes a cylindrical portion (CP) which extends in the axial direction of the shaft and engages with the outer surface of the shaft when the shaft is inserted into the housing, and an end portion cover (EP) which extends in a first direction substantially perpendicular to the axial direction of the shaft and has a first end at a tip of the cylindrical portion and a second end at a point which covers a penetration end surface of the shaft (see Fig. 1), wherein the cylindrical portion is rotatable relative to the shaft in such a manner as to be in contact with the shaft (see Fig. 1), wherein the end portion cover and the penetration end surface are configured to define a space there between in the axial direction of the shaft, in such a manner as to be free from contact there between, and the first end and second end of the end portion cover are aligned on a line substantially parallel to the axial direction of the shaft, and wherein the shaft defines an inner cylindrical face which extends to the penetration end surface of the shaft, wherein the end portion cover is part of the cover that covers the motor, and wherein the tip of the cylindrical portion (the rounded portion thereof) is inclined toward the shaft in a free/formed state, note Fig. 1 along with the associated description thereof, except for explicitly stating that the end portion extends in a first direction more inwardly than the inner cylindrical face of the shaft.

Art Unit: 2872

Oesterholt et al teaches it is well known to use covers having a cylindrical portion which extends in an axial direction of a shaft (101) and an end portion cover having an inclined tip which extends in a first direction more inwardly than the inner cylindrical face of the shaft, wherein the cylindrical portion and the end portion form substantially an L-shape in cross section (see Fig. 4) in the same field of endeavor for the purpose of obtaining a seal.

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the end portion cover of Ishizaki to include an end portion cover having an inclined tip which extends in a first direction more inwardly than the inner cylindrical face of the shaft, as taught by Oesterholt et al, in order to prevent debris from entering the motor mechanism.

7. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Ricky D. Shafer whose telephone number is (571) 272-2320. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

RDS September 29, 2007